

787x3130
Indoor Panel Directional Antenna
VH-Pol 4-port 6/9dBi
698-960 / 1425-4000



Panel Indoor 698-960/1425-4000 6/9dBi

| Type | 78713130 | | 78733130 |
|----------------------------|---------------------|--------------|-----------|
| Frequency (MHz) | 698-960 | 1425-2700 | 3300-4000 |
| Gain (dBi) | 5.5 | 8.5 | 7.9 |
| VSWR | ≤ 2.0 | ≤ 2.0 | ≤ 2.0 |
| Polarization | V-H | | |
| PIM3 (dBc, @2x43dBm) | ≤ -153 | | |
| Isolation (dB) | ≥ 12 | ≥ 20 | ≥ 24 |
| Front-to-Back Ratio (dB) | ≥ 7 | ≥ 13 | ≥ 10 |
| Horizontal Beamwidth (°) | 130-85 | 95-58 | 65-33 |
| Vertical Beamwidth (°) | 108-78 | 83-45 | 90-25 |
| Input Impedance (ohm) | 50 | | |
| Max. Input Power (W) | 50 | | |
| Lightning Protection | DC Grounded | | |
| Connector | 4 x 4.3-10 Female | 4 x N Female | |
| Dimension (mm) | 385 x 315 x 68 | | |
| Weight (kgs) | Approx. 1.5 | | |
| Reflector Material | Aluminum and PCB | | |
| Radome Material | ABS (UV Stabilized) | | |
| Operating Temperature (°C) | -40 to +65 | | |

