

## 74212012

### Log Periodic Antenna V-Pol 2-port 11dBi 690-4000

### Log Periodic Antenna 690-4000 10/11dBi

Type	74212012				
Frequency Range (MHz)	690-960	960-1695	1695-2170	2170-2690	3300-3800
Gain (dBi, typ.)	9.5	10.5	11.0	11.0	10.5
VSWR	≤ 1.8	≤ 1.6	≤ 1.6	≤ 1.6	≤ 1.6
Polarization	Vertical / Horizontal				
PIM3 (dBc), @2x43dBm	≤ -150				
Horizontal Beamwidth (°)	68	65	61	58	65
Vertical Beamwidth (°)	53	50	48	45	53
Isolation (dB)	≥ 20	≥ 20	≥ 28	≥ 28	≥ 28
Front-to-Back Ratio (dB)	≥ 20	≥ 20	≥ 25	≥ 25	≥ 25
Input Impedance (Ω)	50				
Max. Input Power per port (W)	200				
Total antenna power (W)	350				
Lightning Protection	DC Grounded				
Connector Type	2 x 4.3-10 Female				
Dimension (mm)	300 x 300 x 785				
Weight (kgs)	6.5				
Reflector Material	Aluminum				
Radome Material	Fiber Glass				
Rated Wind Velocity (km/h)	200				
Operating Temperature (°C)	-40 to +65				
Mounting	Pole Mount for Ø38 to Ø52 included				
Wind Load (N) (@150km/h Wind Speed)	Frontal: 25.5   Lateral: 143.1   Rearside: 41.8				
Complaint to Environmental Standards	Dry Heat	GB/T 2423.2		(IEC 60068-2-2)	
	Cold	GB/T 2423.1		(IEC 60068-2-1)	
	Damp Heat	GB/T 2423.3		(IEC 60068-2-78)	
	Change of Temp.	GB/T 2423.22		(IEC 60068-2-14)	
	Salt Mist	GB/T 2423.17		(IEC 60068-2-11)	
		GB/T 10125		(ISO 9227)	
	Ingress Protection	GB/T 4208		(IEC 60529)	
	Vibration	GB/T 2423.10		(IEC 60068-2-64)	
Drop Test	GB/T 2423.8 & 4857.5		Drop Test (ISO 2248)		

