

787x3130

Indoor Panel Antenna
 HV-Pol 4-port 6/9dBi
 698-4200

Indoor Panel
698-4000 6/9dBi

Type	78713130		78733130
Frequency (MHz)	698-960	1425-2700	3300-4200
Gain (dBi)	6.0	8.6	7.3
VSWR	≤ 2.0	≤ 2.0	≤ 2.0
Polarization	H-V		
PIM3 (dBc, @2x43dBm)	≤ -153		NA
Isolation (dB)	≥ 12	≥ 20	≥ 24
Front-to-Back Ratio (dB)	≥ 12	≥ 21	≥ 13
Horizontal Beamwidth (°)	86	61	48
Vertical Beamwidth (°)	73	58	33
Input Impedance (ohm)	50		
Max. Input Power (W)	50		
Lightning Protection	Outer conductor of the connectors is DC grounded Inner conductor of the connectors is not DC grounded		
Connector	4.3-10 female	N female	
Dimension (mm)	393 x 317 x 80		
Weight (kgs)	Approx. 1.74		
Reflector Material	Aluminum and PCB		
Radome Material	ABS (UV Stabilized)		
Operating Temperature (°C)	-40 to +65		
Mounting	Fixed wall mounting bracket included		
Optional accessory (*order separately)	Universal Mounting Bracket 70010008 Wall mount: ±25° horizontal swivel & +27°/-35° vertical tilt Pole mount: ±45° horizontal swivel; pole size Ø38-Ø52mm		

