

**78211380****2:2 Hybrid Combiner  
380-3800Mhz**Hybrid Combiner 2-in/2-out  
PIM -160dBc  
380-3800Mhz

| Type                                | 78211380                      |
|-------------------------------------|-------------------------------|
| Frequency (MHz)                     | 380-3800                      |
| Insertion Loss (dB)                 | 3 ± 1.0                       |
| VSWR                                | ≤ 1.25                        |
| Isolation (dB)                      | ≥ 23                          |
| PIM3 (dBc, @2x43dBm)                | ≤ -160                        |
| Input Impedance (ohm)               | 50                            |
| Max. Input Power (W)                | 500                           |
| Peak Power (W)                      | 1,500                         |
| Connector                           | 4.3-10 Female                 |
| Weight (kgs)*                       | 1.1 ± 0.55                    |
| AISG/DC Bypass Path<br>(2500mA Max) | IN1 ↔ OUT1<br>IN2 ↔ OUT2      |
| Dimension (mm)**                    | 188.8 x 48 x 46               |
| Ingress Protection Class            | IP65 (for outdoor and indoor) |
| Operating RH (%)                    | ≤ 95                          |
| Operating Temperature (°C)          | -40 to +65                    |
| Mounting                            | Wall Mount                    |
| Colour                              | Light Grey                    |

