


80011848

**Outdoor Mini Omni
617-960/1710-6000
3/5/5/5dBi**


Outdoor MiMO Omnidirectional
Antenna VV-Pol
2-port
3/5/5/5dBi
617-960 / 1710-6000

Type	80011848			
Frequency range (MHz)	617-960	1710-2700	3300-4000	4900-6000
Maximum Gain (dBi)	3	5	5	5
PIM3 (dBc, @2x43dBm)	≤ -153			
Horizontal Beamwidth (°)	360			
Vertical beam width (°)	85	70	55	28
Input Impedance (ohm)	50			
Max. Input Power (W)	50			
VSWR	≤ 2.5			
Connector	2 x 4.3-10 Female			
Dimension (mm)	Ø82 x 200			
Weight (kgs)	0.8 (including bracket)			
Lightning protection	All metal parts of the antenna and the mounting kit are DC grounded (the inner conductor is not DC grounded)			
Reflector Material	Aluminum			
Radome Material	UPVC (white)			
Rated wind velocity (m/s)	40			
Operating Temperature (°C)	-40 to +65			
Suitable pole diameter	Ø25- Ø50			
Mounting bracket	included			

617~960MHz Typical pattern:



1710~2700MHz Typical pattern:



3300~6000MHz Typical pattern:

